



MEASUREMENTS FOR SOLID SPRUCE MAST or similar

BOOM: SOLID 14'-6" OA, for roller reefing to be tapered from 3 1/2" dia at gooseneck to 4 1/4" at aft end, to prevent 'boom droop' when reefed.
 For SLAB REEFING square sided 3 1/4" x 4 1/2" at aft end.
 GAFF: Solid spruce x 2 3/4" dia at jaws to 2 1/4" at peak.
 For BOWSPRIT see SHEET 4

SAIL	LUFF	LEECH	FOOT	HEAD	AREA FT ²	RECOMM'D WT. LBS
MAINSAIL	18'-2"	26'-2"	13'-6"	10'-0"	227	7 oz.
FORESTAYS'L	21'-6"	18'-11"	16'-6"	-	101	7 oz.
WORKING JIB	23'-10"	18'-9"	10'-9"	-	89	7 oz.
TOPSAIL	13'-0"	-	9'-9"	7'-4"	36	4 1/2 oz.

STANDING RIGGING	No.	PSWR	ST. STEEL
TOPMAST FORESTAY	1	3/4" circ 7x7	5/8" circ 1x19
INNER FORESTAY	1	1/8" " 7x7	3/4" " "
MAIN (LOWER) SHROUDS	2	1/8" " 7x7	3/4" " "
TOPMAST SHROUDS	2	3/4" " 7x7	5/8" " "
RUNNING BACKSTAYS	2	3/4" " 7x7	5/8" " "

CLR 10' 4 1/2"