



Non-Slip Deck Covering  
Should a non-slip deck covering be required - Epoxy Resin paint & glass fibre cloth is recommended. The latter should be applied first and the epoxy resin applied as follows:  
1) (25) up the doghouse side - Side Decks  
2) (25) down the doghouse side - Doghouse top  
3) (25) down the hull - Side Decks aft  
4) (25) down the hull - Main Deck forward.

Note: All Gunwale Beams 1 1/2" x 1 1/2" except those marked \* which are 2 1/2" x 1 1/2"

Thin backing plate to be fitted to obtain a good fit between bilge keel and gunwale and for planking.

Note: Use backing compound between bilge keel and gunwale before bolting up.

MIDSHIP SECTION  
Scale: 1" = 1' foot  
(Looking Forward)

SECTION THROUGH MAIN GUNWALE  
Scale: Full Size

SECTION THROUGH DOGHOUSE SIDE AND COCKPIT COAMING  
Scale: Full Size

SECTION THROUGH CHINE  
Scale: Full Size

SECTION THROUGH BILGE STRINGER  
Scale: Full Size

SECTION THROUGH HOG AND KEEL  
Scale: 1/2 Full Size

SECTION THROUGH DOGHOUSE CARLIN ETC.  
Scale: Full Size

Section through Fore and Aft Coamings  
Scale: Full Size

Section through Side Coamings  
Scale: Full Size

SECTION THROUGH MAIN HATCH AND RUNNER  
Scale: Full Size

Double Skin Planking

Single Skin Planking

Section through Hatch Cover