



SEE SHEET NO 6 FOR DETAILS OF STEM.

DOUBLE BLOCK WITH 2" MINIMUM SHEAVE DIA SHACKLED TO 3/8" EYE BOLT IN STEM. LEAD TACKLE OFF TOP OF SHEAVE & AFT TO 8" WOOD CLEAT ON TOP OF TRUNK.

SEAT BACK CHOCKS (SHEET 6) ON TRUNK & PLANKING.

3/16" GALV'D SHORT LINK CHAIN. SINGLE BLOCK WITH BECKET. 2" MINIMUM SHEAVE DIA. TACKLE. 1/4" CIRC HEMP.

STOP PIN TO PREVENT C-P FROM SWINGING FOR'D IF TACKLE PARTS.

1 1/2" X 8 B.S. SPACED 3"

BLADE HOISTING LINE 1/2" CIRC. FLEX WIRE ROPE 2.6' LONG WITH EYESPLICE BOTH ENDS. SPLICE 2.6' OF 1" CIRC HEMP INTO TOP EYE & ATTACH LOWER END TO BLADE WITH 1/4" D SHACKLE.

OUTBOARD BRACKET ST'D.

TRANSOM KNEE. 1" MAHOG WITH 3/8" PLY CHEEKS BOTH SIDES UP TO LINE X. FASTEN CHEEKS WITH 1" X 1/4" C.N.

FASTEN CHAIN PLATES TO OUTSIDE OF HULL & BOLT THRU TO 2" X 3/4" PAD FITTED BETWEEN GUN'L & CHINE

SECTION THRU STEM.

2 - 1 1/2" X 10 B.S.

1/4" SIDED FLOOR. OAK OR MAHOG. TOP EDGE LEVEL WITH TOP OF CHINE. FASTEN FLOORS UP THRU HOG & PLANK WITH 2" X 10 B.S. P.S. TO PLANKING WITH 1 1/2" X 8 B.S. SPACED 3".

2" X 7/8" BEARERS FITTED OVER CHINE & TRUNK LOG TO BRING TOP EDGES LEVEL FORE & AFT WITH TOP EDGE OF FORD FLOOR. FIT 2" X 7/8" BEARER ON FACE OF BULKHEAD FLOOR WITH TOP EDGE 2" ABOVE HOG.

1/4" SIDED FLOOR. OAK OR MAHOG. TOP EDGE 3" ABOVE HOG. FIT 2" X 7/8" BEARER ON FACE OF BULKHEAD FLOOR WITH TOP EDGE 2" ABOVE HOG.

2" X 7/8" BEARER ON AFT SIDE OF BULKHEAD. 2" X 7/8" BEARERS FITTED TO CHINE (AFT ONE TO PLANK) WITH TOP EDGES LEVEL FORE & AFT 3/8" BELOW D.W.L.

2" X 7/8" LEGS SCREWED TO CENTRE OF BEARERS & RESTING ON HOG.

BERTH BOTTOMS JOINT ON FORD TRUNK SIDES & MADE UP OF 3 SECTIONS OF FLOOR & CENTRE BEARER. SHAPE INSIDE OF PLANKING.

3/8" PLYWOOD PER SIDE TO EASY FIT BETWEEN

THIS SECTION LOWER THAN BERTH BOTTOMS & MADE UP FROM 1/2" PLY IN TWO SECTIONS. JOINT ON FORE & AFT CENTRE LINE.

CENTRE BOARDS TO WIDTH OF 12" CLEATED TOGETHER TO FORM TRAP. 3 CLEATS 1/2" X 3/8" FASTEN TO BOARDS WITH 1/2" X 1/2" C.N. TURNED. FLOORING 5/8" THICK PINE, MAHOG OR TEAK. WIDTH BETWEEN 3" & 6" SCREW FIXED BOARDS TO BEARERS WITH 1 1/2" X 8 B.S. 2 PER BOARD/BEARER.

LOCKER FRONT SCREWED TO EDGE OF FIXED FLOORING WITH 1 1/2" X 8 B.S. SPACED ABOUT 6". LOCKER TOPS 1/2" PLY WITH JOINT ON THIS LINE 1/2" OVERHANG ON INBOARD EDGE. OUTBOARD EDGE FITTED TO INSIDE OF PLANKING.

LOCKER P & S WITH LIFT OUT FRONT.

DETAIL OF CABIN DOOR SLIDES. BOTH PANELS SAME SIZE, BUT ONLY TOP SLIDE HAS WEATHER STRIP ON LOWER EDGE. SEE DETAIL "A" BELOW. BOTH SLIDES TO BE AN EASY FIT IN GROOVES. SEE DETAIL "C" BELOW.

3/4" HALF ROUND MAHOG BEADING. FASTEN WITH 1" X 1/4" C.N. SPACED 3".

CABIN SIDE FASTENED WITH 1" X 8 B.S. SPACED 2 1/2"

CABIN CARLING 2" X 3/4" MAHOG.

DETAIL OF CABIN SIDE & CARLING.

1/8" CLEAR PERSPEX GLAZING 3/4" X 1/8" BRASS RING FASTENED WITH 11 - 3/8" X 6 B.S.

1" X 14 C.N. SPACED 2 1/2"

1" HALF ROUND ASH, O.R. ELM OR MAHOG. FASTEN WITH 1 1/4" X 8 B.S. SPACED 4"

1 1/4" X 12 C.N. SPACED 3" TURNED ON INSIDE.

FOOTRAIL TO FORE DECK 3/4" MAHOG. OFF TO 5/8" ON TOP EDGE. 1" X 8 B.S. SPACED 6"

2" X 10 B.S.

1 1/4" X 8 B.S. SPACED 4"

SIDE FRAME.

BEAM.

BEAM.

CABIN SIDE. 1" SECTION MOULDING FASTENED TO DECK WITH 1" X 8 B.S. SPACED 3"

1" X 8 B.S. SPACED 3"

1" X 6 B.S. SPACED 3"

1 1/2" X 8 B.S. SPACED 3"

1" X 8 B.S. SPACED 3"

1" X 8 B.S. SPACED 3"

DETAIL B.

DETAIL C.

DETAIL A.

CABIN SILL. 1 1/2" X 10 B.S. SPACED 8"

CABIN DOOR POSTS.

JOINT OF CABIN DOOR SLIDES.

2" X 10 B.S. SPACED 6"

1" X 8 B.S. SPACED 3" IN WAY OF STRUK.

SECTION THRU KEEL & C-P TRUNK.

1" X 14 C.N. SPACED 1 1/2" TURNED ON INSIDE.

SECTION THRU BUTT STRAP JOINT. USED FOR ALL JOINTS IN PLYWOOD PANELS.

SECTIONS OF GUN'L, CABIN SIDE & UPPER CHINE. 1 1/4" X 12 C.N. SPACED 3" TURNED ON INSIDE.

SECTION OF GUN'L ON BULKHEAD OR FRAME. 2" X 10 B.S. SPACED 6"

SECTION OF GUN'L ON DECK BEAM. HOG. MAHOG 4 1/2" X 3/4". KEEL. E. OAK OR MAHOG. 2 3/4" X 1 1/2".

SECTION SHOWING METHOD OF FASTENING CABIN SIDE EXTENSIONS FOR'D OF COAMING & AFT OF BULKHEAD.

SECTIONS OF LOWER CHINE, HOG & KEEL. 1 1/4" X 12 C.N. SPACED 3" TURNED ON INSIDE.