



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

---

### SECTION 1: IDENTIFICATION

---

#### GHS PRODUCT IDENTIFIERS:

**PRODUCT NAME:** Bristol Finish Traditional Amber Urethane High Gloss  
**SYNONYMS, TRADE NAMES:** Acrylic Urethane Base – Part A, Traditional Amber Resin  
**OTHER MEANS OF IDENTIFICATION:** Not available

#### RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

**USES:** Traditional Amber Wood Coating System  
**RESTRICTIONS ON USE:** None Identified

#### SUPPLIER'S DETAILS:

**MANUFACTURER/SUPPLIER:** Endurance Technologies, Inc.  
275 Bridge Point Drive  
South Saint Paul, MN 55075, USA  
**TELEPHONE:** +1 651 451 8000  
**FACSIMILE:** +1 651 451 9728

**CONTACT PERSON:** Eric Frank

#### EMERGENCY PHONE NUMBER:

**INFOTRAC (24 HRS): USA & CANADA** 1 800 535 5053  
**INFOTRAC (24 HRS): INTERNATIONAL** +1 352 323 3500

---

### SECTION 2: HAZARDS IDENTIFICATION

---

#### GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE:

Flammable liquids	Category 3, H226
Acute toxicity, inhalation:	Category 4, H332
Acute toxicity, oral:	Category 4, H302
Skin irritation:	Category 2, H315
Specific target organ toxicity:	Single Exposure Category 3, H335, H336
Toxic to Reproduction	Category 1, H360, H362
Skin sensitization:	Category 1, H317
Hazardous to the aquatic environment:	Acute Category 3, H402
Hazardous to the aquatic environment:	Chronic Category 3, H412
Acute toxicity, dermal	Category 4, H312

#### GHS LABEL ELEMENTS:

#### HAZARD SYMBOLS:



#### SIGNAL WORDS:

Danger

#### HAZARD STATEMENTS:

H226 Flammable liquid and vapor.



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H360 May damage fertility or the unborn child.  
H362 May cause harm to breast-fed children.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS:

**PREVENTION:** P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe mists.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in well ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, clothing, and eye/face protection.

**RESPONSE:** P370+P378 In case of fire: Use water spray, carbon dioxide, dry chemical or alcohol foam to extinguish.  
P301+P330+P312 IF SWALLOWED: Rinse mouth. Call POISON CENTER if you feel unwell.  
P303+P361+P364+P353+P352 IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/shower. Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical attention.  
P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call POISON CENTER if you feel unwell.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical attention.  
P308+P313 IF exposed or concerned: Get medical advice/attention.

**STORAGE:** P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P235 Keep cool.  
P405 Store locked up.

**DISPOSAL:** P501 Dispose of contents and containers in accordance with local, regional and international regulations.

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS) – Annex III



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME:	CAS NUMBER:	CONTENT:
2-Heptanone	110-43-0	15-40%
Aliphatic dibasic esters	Mixture	1-20%
Xylene	1330-20-7	15-40%

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

### SECTION 4: FIRST-AID MEASURES

#### DESCRIPTION OF NECESSARY FIRST-AID MEASURES:

- INHALATION:** If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
- SKIN:** Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. Get medical attention if symptoms occur.
- EYES:** Immediately flush eyes with plenty of clean water for an extended time, not less than fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion.
- INGESTION:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

#### MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED:

- SYMPTOMS:** Irritation. Pre-existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

#### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF NECESSARY:

- TREATMENT:** Treat symptomatically.

### SECTION 5: FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA:

- SUITABLE:** Use water spray, foam, dry chemical or carbon dioxide.
- UNSUITABLE:** None known.

#### SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

**UNUSUAL FIRE & EXPLOSION HAZARDS:** Flammable liquid and vapor. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of gases to explosive levels. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Do not reuse container without commercial cleaning and reconditioning.



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

**HAZARDOUS COMBUSTION PRODUCTS:** Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See Section 10 Hazardous decomposition products for additional information.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear self-contained breathing apparatus (SCBA) equipped with a full face piece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations. See section 9 for additional information.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

---

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:** See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

**ENVIRONMENTAL PRECAUTIONS:** Do not flush product into public sewer, water systems or surface waters.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:** Stop leak if without risk. Move containers from spill area. Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse. Eliminate sources of ignition. Use only non-combustible material for cleanup. Flush spill area with water spray after clean up. Use water mist or spray to disperse vapors. Stay up wind of spill. Ventilate spill area.

---

### SECTION 7. HANDLING AND STORAGE

---

**PRECAUTIONS FOR SAFE HANDLING:** As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Use under well-ventilated conditions. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

**CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:** Keep away from heat, sparks and open flames. Store dry at 15-40°C, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Empty container contains residual product which may exhibit hazards of product. Do not reuse empty container without commercial cleaning or reconditioning.

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**CONTROL PARAMETERS:**

**OCCUPATIONAL EXPOSURE LIMITS:**

INGREDIENT NAME:	CAS NUMBER	TYPE	EXPOSURE LIMITS
2-Heptanone	110-43-0	ACGIH TLV-TWA OSHA PEL-TWA	50 ppm 100 ppm
Aliphatic dibasic esters	Mixture	Not available	Not available



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

Xylene	1330-20-7	OSHA PEL-PEL	100 ppm, 435 mg/m <sup>3</sup>
		OSHA PEL-STEL	150 ppm, 655 mg/m <sup>3</sup>
		OSHA PEL-TWA	100 ppm, 435 mg/m <sup>3</sup>
		ACGIH TLV-TWA	100 ppm
		ACGIH TLV-STEL	150 ppm

**APPOPRIATE ENGINEERING CONTROLS:** Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain air concentrations below occupational exposure standards. When necessary use mechanical handling to reduce human contact with materials.

### INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE):

<b>EYE/FACE PROTECTION:</b>	Safety glasses or goggles required.
<b>SKIN PROTECTION:</b>	Wear chemical resistant (impervious) gloves; PVC, neoprene, nitrile rubber, EVAL, butyl rubber. Wear chemical resistant protective clothing. Use good laboratory/workplace procedures including personal protective clothing: lab coat and protective gloves.
<b>RESPIRATORY PROTECTION:</b>	Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable exposure limit(s) of any chemical substance listed in this SDS.
<b>GENERAL PROTECTION:</b>	Eyewash fountains and safety showers are recommended in the work area.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>APPEARANCE:</b>	Liquid	<b>UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:</b>	Lower: 1
<b>COLOR:</b>	Clear amber	<b>VAPOUR PRESSURE:</b>	0.56 kPa (4.2 mm Hg) at room temp
<b>ODOUR:</b>	Pungent, sweet	<b>VAPOUR DENSITY:</b>	Not available
<b>ODOUR THRESHOLD:</b>	Not available	<b>RELATIVE DENSITY:</b>	0.95
<b>PH:</b>	Not available	<b>SOLUBILITY(IES):</b>	Not available
<b>MELTING POINT/ FREEZING POINT</b>	Not available	<b>PARTITION COEFFICIENT (n-octanol/water):</b>	Not available
<b>INITIAL BOILING POINT AND BOILING RANGE:</b>	Not available	<b>AUTO-IGNITION TEMPERATURE:</b>	Not available
<b>FLASH POINT:</b>	39°C (102°F) Closed cup	<b>DECOMPOSITION TEMPERATURE:</b>	Not available
<b>EVAPORATION RATE:</b>	Not available	<b>VISCOSITY:</b>	Not available
<b>FLAMMABILITY (SOLID, GAS):</b>	Not available	<b>VOLATILITY:</b>	57% (v/v), 50.78% (w/w)
<b>% SOLID:</b>	42.73 (w/w)		

---

## SECTION 10. STABILITY AND REACTIVITY

---



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

**REACTIVITY:** Exothermic reactions including polymerization may occur in contact with amines, strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

**CHEMICAL STABILITY:** This product is stable.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Exothermic reactions including polymerization may occur in contact with amines, strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

**CONDITIONS TO AVOID:** Excessive heat, impact, friction, sparks, flame and sources of ignition.

**INCOMPATIBLE MATERIALS:** Avoid strong acids, bases, and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

---

**INFORMATION ON THE LIKELY ROUTES OF EXPOSURE:** Eyes, skin, inhalation and ingestion.

**SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:**

**EYES:** May cause eye irritation.

**SKIN:** Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

**INHALATION:** Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

**INGESTION:** Harmful if swallowed.

**DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE:** May damage fertility or the unborn child. May cause harm to breast-fed children.

**ACUTE TOXICITY:**

CHEMICAL NAME	LC <sub>50</sub> INHALATION (RAT)	LD <sub>50</sub> ORAL (RAT)	LD <sub>50</sub> DERMAL (RABBIT)
2-Heptanone	>16.7 mg/L	>1,600 mg/kg	>2,000 mg/kg
Aliphatic dibasic esters	>20 mg/L	>5,000 mg/kg	>2,000 mg/kg
Xylene	>20 mg/L	>5,000 mg/kg	>2,000 mg/kg

**CORROSION / IRRITATION / SENSITIZATION INFORMATION:**

**SKIN CORROSION/IRRITATION:** Skin irritation – Category 2

**SERIOUS EYE DAMAGE/IRRITATION:** Information is not available.

**RESPIRATORY OR SKIN SENSITIZATION:** Skin sensitization – Category 1

**CARCINOGENICITY / MUTAGENICITY / REPRODUCTIVE TOXICOLOGY INFORMATION:**

**GERM CELL MUTAGENICITY:** Information is not available.

**CARCINOGENICITY:** Information is not available.

**REPRODUCTIVE TOXICITY:** Category 1

**SPECIFIC TARGET ORGAN TOXICITY (STOT):**

**STOT-SINGLE EXPOSURE:** Category 3

**STOT-REPEATED EXPOSURE:** Information is not available.

**ASPIRATION HAZARD:** Information is not available.



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

**OTHER INFORMATION:** Additional information is not available.

---

### SECTION 12. ECOLOGICAL INFORMATION

---

**TOXICITY:**

CHEMICAL NAME	TEST	SPECIES	RESULT
2-Heptanone	Not available	Not available	Not available
Aliphatic dibasic esters	Not available	Not available	Not available
Xylene	LC50 (96 hrs)	Fish	>100 mg/L
	EC50 (48 hrs)	Daphnia Magna	>100 mg/L

N/E = Not established (no exposure limits established for listed substances for listed country/region/organization).

**PERSISTENCE AND DEGRADABILITY:**

CHEMICAL NAME	TEST	PERIOD	RESULT
2-Heptanone	Not available		
Aliphatic dibasic esters	Not available		
Xylene	Not available		

**BIOACCUMULATIVE POTENTIAL:**

CHEMICAL NAME	Log P <sub>ow</sub>	BCF	POTENTIAL
2-Heptanone	Not available	Not available	Not available
Aliphatic dibasic esters	Not available	Not available	Not available
Xylene	Not available	Not available	Not available

**MOBILITY IN SOIL:**

CHEMICAL NAME	SOIL/WATER PARTITION COEFFICIENT (K <sub>oc</sub> )
2-Heptanone	Not available
Aliphatic dibasic esters	Not available
Xylene	Not available

**OTHER ADVERSE EFFECTS:** Additional information is not available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

---

**DISPOSAL METHODS:** Dispose of unused contents (incineration) in accordance with national and local regulations. Dispose of container in accordance with national and local regulations. Ensure the use of properly authorized waste management companies, where appropriate. See section 8 for recommendations on the use of personal protective equipment.

---

### SECTION 14. TRANSPORTATION INFORMATION

---

**UN NUMBER:** UN1263

**UN PROPER SHIPPING NAME:** Paint

**TRANSPORT HAZARD CLASS:**



# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

<b>U.S. DOT HAZARD CLASS:</b>	Combustible Liquid
<b>CANADA TDG HAZARD CLASS:</b>	3
<b>EUROPE ADR/RID HAZARD CLASS:</b>	3
<b>IMDG CODE (OCEAN) HAZARD CLASS:</b>	3
<b>ICAO/IATA (AIR) HAZARD CLASS:</b>	3

**PACKING GROUP:** III

**ENVIRONMENTAL HAZARDS:**

<b>MARINE POLLUTANT:</b>	No
<b>HAZARDOUS SUBSTANCE (USA):</b>	No

**SPECIAL PRECAUTIONS FOR USER:** Information is not available.

**TRANSPORTING IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:**  
Information is not available.

**LABEL FOR CONVEYANCE:**



**OTHER INFORMATION:** In containers of 119 gallons or less this product is not regulated by the DOT. Label/Placard: exception 173.150(f) applies.

---

### SECTION 15. REGULATORY INFORMATION

---

**SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION:**

U.S. Superfund Amendments and Reauthorization Act (SARA) – SARA Section 313	Xylene (CAS 1330-20-7)
CERCLA RQ	100 LBS, Xylene (CAS 1330-20-7)
EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV – List of substances subject to authorization, Substances of very high concern	None of the components are listed.
Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	None of the components are listed.

**OTHER REGULATIONS:** Additional information is not available.

**CHEMICAL INVENTORIES:**

Canadian Domestic Substances List (DSL):	Y
Canadian Non-Domestic Substances List (NDSL):	N
European Inventory of Existing Chemical Substances (EINECS):	Y
European List of Notified Chemical Substances (ELINCS):	N
U.S. Toxic Substances Control Act (TSCA):	Y





# SAFETY DATA SHEET

## TRADITIONAL AMBER URETHANE HIGH GLOSS

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory; 2) no information is available; or 3) the component has not been reviewed.

---

### SECTION 16. OTHER INFORMATION

---

**REVISION DATE:** February 6, 2019

**LEGEND:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- ADR/RID: European dangerous goods transport road and rail regulations
- CAS No: Chemical Abstract Service Registry Number
- DOT: Department of Transportation (U.S.)
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization
- IMDG: International Maritime Dangerous Goods code
- OEL: Occupational Exposure Limits
- OSHA: Occupational Safety and Health Administration (U.S.)
- PEL: Permissible Exposure Limit
- RQ: Reportable Quantity
- SDS: Safety Data Sheet
- STEL: Short Term Exposure Limit (15 minute Time Weighted Average)
- TDG: Canadian Transportation of Dangerous Goods Act and Regulations
- UN: United Nations
- U.S.: United States

**USERS RESPONSIBILITY/DISCLAIMER OF LIABILITY:**

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.